

CERTIFICATE OF ADMITTANCE

No. 4357/2021

Based on art. 7 paragraph 2 of the Act of 24 August 1991 on fire protection
Centrum Naukowo-Badawcze Ochrony Przeciwożarowej im. Józefa Tuliszowskiego
Państwowy Instytut Badawczy at the request of:

Intelight Sp. z o. o.
ul. Gwiazdzista 19
01-651 Warszawa

states that product:

Luminaire for emergency lighting type STARLET QUAD
Varieties of luminaire are given on page 2 of the certificate of admittance.

manufactured by:

Intelight Sp. z o. o.
ul. Gwiazdzista 19
01-651 Warszawa

in the manufacturing plant:

Intelight Sp. z o. o.
Poczermin 46
09-142 Żaluski

meets the requirements of:

pt. 13.2 of annex to the Regulation of the Minister of the Interior
and Administration of 20 June 2007 on the list of products used for ensuring
public safety or protecting health, life and property, and the principles
of issuing admittance to use these products (Polish Journal of Laws: Dz. U. nr 143
poz. 1002; zm.: Dz. U. z 2010 r. nr 85, poz. 553, z 2018 r. poz. 984,
z 2022 r. poz. 2282)

Documentation:

1. Application for the process of product admittance No. 5972/2021 of 04.01.2021 and application for changing the admittance No. 6190/2021 of 12.07.2021 and No. 7443/2024 of 05.03.2024.
2. Test report No. 855/BA/21 of 04.06.2021, No. 1277/BA/21 of 31.08.2021 and No. 219/BA/24 of 16.05.2024 issued by Zespół Laboratoriów Sygnalizacji Alarmu Pożaru i Automatyki Pożarniczej (BA) CNBOP-PIB.


The certificate of admittance is valid under the condition that the applicant fulfils the requirements defined in the agreement No. 4357/DC/CNBOP-PIB/2021.

Validity period of the admittance:

from **13.06.2024**

until **20.06.2026**

DIRECTOR OF CNBOP-PIB



st. bryg. Paweł Janik, PhD Eng.



Józefów: 13 June 2024

Page 1/3

*This document was originally translated from Polish to English on 14 June 2024.
In case of conflict between the Polish certificate of admittance and this translation, the Polish document shall be binding.*

CERTIFICATE OF ADMITTANCE

No. 4357/2021

TECHNICAL DATA IDENTIFYING THE PRODUCT

Luminaire for emergency lighting type STARLET QUAD in varieties:

Name	Optics	Model	Operation mode	Autonomy	Performance
STARLET QUAD	SO	150	NM	1h	MT
	SC		M	2h	AT
	SQ	250		3h	CT
	SP				
STARLET QUAD	SO	350	NM	1h	MT
	SC			2h	AT
	SP			CT	
STARLET QUAD	SO	350	NM	3h	MT
	SC				
	SP				
STARLET QUAD	SOH	250	NM	1h	MT
	SCH			2h	AT
				3h	CT
STARLET QUAD	SOH	350	NM	1h	MT
	SCH			2h	AT
STARLET QUAD	SOH	350	NM	3h	MT
	SCH				
STARLET QUAD	SO	150	---	---	CB
	SC	250			
	SQ	350			
	SP				
STARLET QUAD	SOH	250	---	---	CB
	SCH	350			

DIRECTOR OF CNBOP-PIB



st. brig. Paweł Janik, PhD Eng.



Józefów: 13 June 2024

Page 2/3

*This document was originally translated from Polish to English on 14 June 2024.
In case of conflict between the Polish certificate of admittance and this translation, the Polish document shall be binding.*

CERTIFICATE OF ADMITTANCE

No. 4357/2021

DANE TECHNICZNE IDENTYFIKUJĄCE WYRÓB

Luminaire for emergency lighting type STARLET QUAD

Varieties of luminaire are given on page 2 of the certificate of admittance.

Type	STARLET QUAD	
	Z - central supply (varieties: CB);	X - self-contained (varieties: MT, AT, CT);
Operation mode	0 - non-maintained; 1 - maintained;	0 - non-maintained; 1 - maintained;
Accessories	E - with non-replaceable lamp	A - including test device; B - includes remote resting mode (varieties: CT); C - includes locking mode (varieties: CT); E - with non-replaceable lamp; F - automatic test gear complying with IEC 61347-2-7, marked as EL-T (varieties: AT, CT);
Rated emergency operating time	not applicable (parameter of supply systems)	60 - 1 hour of emergency operating time; 120 - 2 hours of emergency operating time; 180 - 3 hours of emergency operating time;
Rated supply voltage	230V AC 50Hz, 220V DC	230V AC 50Hz
Protection class against electric shock	II	
Ingress protection rating to dust, solids and water	IP20	
Light source	LED module	
Battery charging time	not applicable (parameter of supply systems)	not exceeding 24 h
Battery charging indication	not applicable (function of supply systems)	yes - LED diode
Adapted to pictograms	no	
Mounting method	surface, recessed	
Mounting surface (in accordance with PN-EN 60598-1)	normally flammable surfaces	
Conditions of use (in accordance with PN-EN 60598-1)	for normal use	
Material of housing	plastic	

Self-contained luminaires in AT and CT varieties are intended for automatic test systems in accordance with the standard PN-EN 62034:2012.

ADDITIONAL CONDITIONS AND COMMENTS:

According to § 17 of the Regulation of the Minister of the Interior and Administration of 20 June 2007 on the list of products used for ensuring public safety or protecting health, life and property, and the principles of issuing admittance to use these products (Polish Journal of Laws: Dz. U. nr 143 poz. 1002; zm.: Dz. U. z 2010 r. nr 85, poz. 553, z 2018 r. poz. 984, z 2022 r. poz. 2282) a product should be marked with the marking of the admittance body and also the number of the certificate of admittance.

The following editions of the standards were used in the admittance process:

- PN-EN IEC 60598-2-22:2022-11
- PN-EN IEC 60598-1:2021-07+A1+A11:2022-12

DIRECTOR OF CNBOP-PIB



st. bryg. Paweł Janik, PhD Eng.



Józefów: 13 June 2024

Page 3/3

*This document was originally translated from Polish to English on 14 June 2024.
In case of conflict between the Polish certificate of admittance and this translation, the Polish document shall be binding.*